

DUO LOCK CLEAT™ Use Instructions

Duo Lock Cleat™ in Trax:

1. Place bottom "flat" surface of Duo Lock Cleat™ on top of Trax surface.
2. Line up the TWO rounded contours on the Duo Lock Cleat™ with TWO round openings on the Trax.
3. Pushing down gently, slide the Duo Lock Cleat™ forward or backward until the Duo Lock Cleat™ drops into the Trax.

NOTES: Make sure the "spring" slide on the Duo Lock Cleat™ is depressed into the round opening on the Trax and the Duo Lock Cleat™ is securely locked into place on Trax. Loads shift & settle; inspect after 10 miles; then every 40/50 miles thereafter (inspect in shorter intervals if on rough bumpy roads or inclement weather). Make sure all connecting points on vehicle are secure.

Move or Remove Duo Lock Cleat™:

1. Using your thumb and fingers, grip the "spring" slide and pull upwards.
2. Slide the Duo Lock Cleat™ forward or backward to unlock and lift the Duo Lock Cleat™ off the Trax.

WARNING: Inspect product before each use. DO NOT USE: If product is deformed, worn, damaged, rusted or not securely installed. Avoid contact with sharp objects, flame or chemicals that may damage or weaken product, as these conditions may result in severe DAMAGE to persons or property. Product is NOT designed nor to be used as a personal restraint, or towing device. USER assumes full responsible for determining product's safe condition and suitability for a particular purpose. **NOTICE TO PURCHASER:** Core Products USA is not responsible for damage or injury caused by improper use of products.