

CARGO COVER EXTENSION STRAPS™ Use Instructions

Attaching the Extension Straps:

For Larger/Taller Loads

1. Connect/attach the Carabineer on the Cargo Safety Cover™ to the D-ring at the end of the Extension Strap.
2. Attach the Carabineer at the opposite end of the Extension Strap to a secure tie down/anchor point.
3. Follow the instructions on the Cargo Safety Cover™ to adjust height.

For Smaller/Shorter Loads

1. Connect/attach the Carabineer on the Cargo Safety Cover™ to the D-ring at the end of the Extension Strap.
2. Grasp the D-ring in the center of the Extension Strap and connect it to the Carabineer on the Cargo Safety Cover™ (as in step 1). NOTE: This secures the strap and keeps the excess length from flapping around.
3. Attach the Carabineer at the opposite end of the Extension Strap to a secure tie down/anchor point.
4. Follow the instructions on the Cargo Safety Cover™ to adjust height.

NOTES: For higher bed loads, four Extension Straps may be needed. Loads shift & settle; inspect after 10 miles; then every 40/50 miles thereafter (inspect in shorter intervals if on rough bumpy roads or inclement weather). Make sure all connecting points on vehicle are secure.

WARNING: Inspect product before each use. DO NOT USE: If product is deformed, worn, damaged, rusted or not securely installed. Avoid contact with sharp objects, flame or chemicals that may damage or weaken product, as these conditions may result in severe DAMAGE to persons or property. Product is NOT designed nor to be used as a personal restraint, or towing device. USER assumes full responsible for determining product's safe condition and suitability for a particular purpose. **NOTICE TO PURCHASER:** Core Products USA is not responsible for damage or injury caused by improper use of products.