

LI'L SPORT™ STRETCH NET Use Instructions

1. Attach the Stretch Net by connecting the molded plastic hooks to tie down points or other suitable points where the molded hooks can be attached.
2. Stretch Net across cargo and secure remaining hooks on all four sides.
3. After all hooks are secured, adjust hooks if needed for proper stretch and holding.

NOTE: Cover must be stretched in order to properly apply tension to hooks and secure goods, however **DO NOT overstretch as doing so may cause injury/damage.**

CAUTION: DO NOT ALLOW COVER/MOLDED HOOKS TO SPRING BACK AS DOING SO CAN CAUSE INJURY OR DAMAGE BY FAST MOVING STRETCH NET AND HARDWARE.

NOTES: Loads shift & settle; inspect after 10 miles; then every 40/50 miles thereafter (inspect in shorter intervals if on rough bumpy roads or inclement weather). Make sure all connecting points on vehicle are secure.

WARNING: Inspect product before each use. **DO NOT USE:** If product is deformed, worn, damaged, rusted or not securely installed. Avoid contact with sharp objects, flame or chemicals that may damage or weaken product, as these conditions may result in severe **DAMAGE** to persons or property. Product is **NOT** designed nor to be used as a personal restraint, or towing device. **USER** assumes full responsible for determining product's safe condition and suitability for a particular purpose. **NOTICE TO PURCHASER:** Core Products USA is not responsible for damage or injury caused by improper use of products.